

SERIE 12CD

12CD

AVO - Pallet truck roller with conductive polyurethane for industry,
diameter 82mm ean 23336

Material: Conductive
Polyurethane

Core: Conductive
polyamide 6

Application field:
Industry

Description:

Pallet truck roller coated with antistatic Polyurethane thread AVOANTISTATIC 91 Shore A and conductive Polyamide 6 centre. Hub on shielded ball bearings.

:

Product line: Antistatic/Conductive

EAN13:8018793233361 **EAN5:**23336 **Article code:**12012CD008270



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 500 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 97

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	82
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Black
Material	Conductive Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	97

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/