

SERIE 116C

116C

AVO - Wheel with 30% glass-filled polyamide 6 for industry, diameter 150mm ean 28506

Material: 30% glass-filled Polyamide 6

Core: Glass-filled polyamide 6

Scope: Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Product line: High temperature, Polyamide

EAN13:8018793285063

EAN5:28506

Article code:G5116C0151BFP



Features

Minimum temperature: -25

Maximum temperature: 120

Dynamic load capacity: 400 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	400
Colour	Blue
Material	30% glass-filled Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/