

SERIE 18AS-B

69ANTB-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 100mm

Material: Avoantistatic Polyurethane

Core: Aluminum

Application field: Industry

Description:

Wheel coated with cast antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all Medium, Heavy and Extra-Heavy duty castors, with twin wheel as well.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13:/ **EAN5:/** **Article code:**09069BA100ACG



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 120 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle
Finishing	Galvanized