

SERIE 18AS-B

## 69ANTB-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 100mm ean 28988

**Material:** Avoantistatic Polyurethane

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel coated with cast antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all Medium, Heavy and Extra-Heavy duty castors, with twin wheel as well.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Antistatic/Conductive

**EAN13:**8018793289887

**EAN5:**28988

**Article code:**09069BA100LCG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 120 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 100                        |
| Band width (mm)             | 40                         |
| Hub width (mm)              | 40                         |
| Hub version                 | Ball bearing               |
| Wheel hole (mm)             | 12                         |
| Bearing seat (mm)           | 32X10                      |
| Dynamic load capacity (DaN) | 120                        |
| Colour                      | Grey                       |
| Material                    | Avoantistatic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 91                         |

### Support data

|                            |                 |
|----------------------------|-----------------|
| Plate size (mm)            | /               |
| Plate hole spacing (mm)    | /               |
| Plate hole size (mm)       | /               |
| Offset (mm)                | 37              |
| Ground clearance (mm)      | 126             |
| Castor hole (mm)           | /               |
| Static load capacity (DaN) | 150             |
| Structure                  | Swivel          |
| Version                    | Axle with brake |
| Brake                      | Front           |
| Plain axle                 | 20X50           |
| Stem type                  | Plain axle      |
| Finishing                  | Galvanized      |