

SERIE 18AS-B

69-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 180mm ean 28966

Material: Avoantistatic Polyurethane

Core: Aluminum

Application field: Industry

Description:

Wheel coated with cast antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all Medium, Heavy and Extra-Heavy duty castors, with twin wheel as well.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Antistatic/Conductive

EAN13:8018793289665

EAN5:28966

Article code:0906900180ACG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	225
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized