

SERIE 18AS-B

## 69-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 200mm ean 28967

**Material:** Avoantistatic Polyurethane

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel coated with cast antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all Medium, Heavy and Extra-Heavy duty castors, with twin wheel as well.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:**8018793289672    **EAN5:**28967    **Article code:**0906900200ACG



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 300 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized