

SERIE 18AS

37ANTF-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 200mm ean 29008

Material: Avoantistatic
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with antistatic Polyurethane thread AVOANTISTATIC 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13:8018793290081

EAN5:29008

Article code:09037FA200ACG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized