

SERIE 18AS-B

## 69-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 80mm

**Material:** Avoantistatic Polyurethane

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel coated with cast antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all Medium, Heavy and Extra-Heavy duty castors, with twin wheel as well.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:/ EAN5:/ Article code:**0906900080LCG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 120 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                            |
|-----------------------------|----------------------------|
| Diameter (mm)               | 80                         |
| Band width (mm)             | 30                         |
| Hub width (mm)              | 40                         |
| Hub version                 | Ball bearing               |
| Wheel hole (mm)             | 12                         |
| Bearing seat (mm)           | 32X10                      |
| Dynamic load capacity (DaN) | 120                        |
| Colour                      | Grey                       |
| Material                    | Avoantistatic Polyurethane |
| Box pieces                  | /                          |
| Hardness scale              | Shore A                    |
| Hardness                    | 91                         |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 100X085    |
| Plate hole spacing (mm)    | 080X060    |
| Plate hole size (mm)       | 8,5X12     |
| Offset (mm)                | 37         |
| Ground clearance (mm)      | 108        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 150        |
| Structure                  | Swivel     |
| Version                    | Plate      |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |