

SERIE 18AS-B

69B-AS

AVO - Wheel with avoantistatic polyurethane and steel castor for industry, diameter 80mm

Material: Avoantistatic Polyurethane

Core: Aluminum

Application field: Industry

Description:

Wheel coated with cast antistatic AVOANTISTATIC polyurethane thread 91 Shore A with aluminium centre. Hub on shielded ball bearings assembled with central spacer. Wheels can be assembled with all Medium, Heavy and Extra-Heavy duty castors, with twin wheel as well.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13:/ EAN5:/ Article code:09069B0080LCG



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 120 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 80 |
| Band width (mm) | 30 |
| Hub width (mm) | 40 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 32X10 |
| Dynamic load capacity (DaN) | 120 |
| Colour | Grey |
| Material | Avoantistatic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 37 |
| Ground clearance (mm) | 106 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 150 |
| Structure | Swivel |
| Version | Axle |
| Brake | / |
| Plain axle | 20X50 |
| Stem type | Plain axle |
| Finishing | Galvanized |