

SERIE 18ACH-AS

18ACH-AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 100mm ean 29058

Material: Avoantistatic Polyurethane

Core: Aluminum

Application field: Industry

Description:

Drive wheel with AVOANTISTATIC polyurethane tread 91 Shore A and mechanically machined cast iron centre, painted black, aluminium or steel. Hub with keyway according to DIN 6885.

Product line: Antistatic/Conductive

EAN13:8018793290586

EAN5:29058

Article code:0918ACHAS100U



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	44
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	FORO 15
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/