

SERIE 18ACH

18ACH-AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 160mm

Material: Avoantistatic Polyurethane **Core:** Aluminum **Application field:** Industry

Description:

Heavy duty drive wheel coated with cast Polyurethane AVOLAN 91 Shore A and black painted mechanical cast iron, aluminium or steel centre. Hub with keyway according to DIN6885.

Product line: Polyurethane

EAN13:/ **EAN5:/** **Article code:**0918ACHAS160U

Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 750 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	30
Hub version	Plain bore
Wheel hole (mm)	30
Bearing seat (mm)	FORO 30
Dynamic load capacity (DaN)	750
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/