

SERIE 18ACH-AS

## 18ACH-AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 200mm ean 29061

**Material:** Avoantistatic Polyurethane

**Core:** Aluminum

**Application field:** Industry

**Description:**

Drive wheel with AVOANTISTATIC polyurethane tread 91 Shore A and mechanically machined cast iron centre, painted black, aluminium or steel. Hub with keyway according to DIN 6885.

**Product line:** Antistatic/Conductive

**EAN13:**8018793290616

**EAN5:**29061

**Article code:**0918ACHAS200U



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 1100 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	30
Bearing seat (mm)	FORO 30
Dynamic load capacity (DaN)	1100
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/