

SERIE 14CH-AS

14CH-AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 250mm ean 29049

Material: Avoantistatic Polyurethane

Core: Cast Iron

Application field: Industry

Description:

Drive wheel with AVOANTISTATIC polyurethane tread 91 Shore A and centre in black painted mechanical cast iron, aluminium or steel. Hub with keyway according to DIN 6885.

Product line: Antistatic/Conductive

EAN13:8018793290494 **EAN5:**29049 **Article code:**09014CHAS253U



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 1800 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	80
Hub width (mm)	80
Hub version	Plain bore
Wheel hole (mm)	40
Bearing seat (mm)	/
Dynamic load capacity (DaN)	1800
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/