

SERIE 18ACH-AS

18ACH-AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 250mm ean 29063

Material: Avoantistatic Polyurethane

Core: Aluminum

Application field: Industry

Description:

Drive wheel with AVOANTISTATIC polyurethane tread 91 Shore A and mechanically machined cast iron centre, painted black, aluminium or steel. Hub with keyway according to DIN 6885.

Product line: Antistatic/Conductive

EAN13:8018793290630

EAN5:29063

Article code:0918ACHAS250U



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1400 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	60
Hub version	Plain bore
Wheel hole (mm)	25
Bearing seat (mm)	FORO 25
Dynamic load capacity (DaN)	1400
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/