

SERIE 14CH-AS

## 14CH-AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 300mm ean 29053

**Material:** Avoantistatic Polyurethane

**Core:** Cast Iron

**Application field:** Industry

**Description:**

Drive wheel with AVOANTISTATIC polyurethane tread 91 Shore A and centre in black painted mechanical cast iron, aluminium or steel. Hub with keyway according to DIN 6885.

**Product line:** Antistatic/Conductive

**EAN13:**8018793290531

**EAN5:**29053

**Article code:**09014CHAS308U



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 2500 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	300
Band width (mm)	80
Hub width (mm)	80
Hub version	Plain bore
Wheel hole (mm)	72
Bearing seat (mm)	/
Dynamic load capacity (DaN)	2500
Colour	Grey
Material	Avoantistatic Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/