

SERIE 14CH-AS

14CH-AS

AVO - Wheel with avoantistatic polyurethane for industry, diameter 400mm ean 29055

Material: Avoantistatic Polyurethane

Core: Steel

Application field: Industry

Description:

Drive wheel with AVOANTISTATIC polyurethane tread 91 Shore A and centre in black painted mechanical cast iron, aluminium or steel. Hub with keyway according to DIN 6885.

Product line: Antistatic/Conductive

EAN13:8018793290555 **EAN5:**29055 **Article code:**09014CHAS450U



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 4400 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|----------------------------|
| Diameter (mm) | 400 |
| Band width (mm) | 150 |
| Hub width (mm) | 150 |
| Hub version | Plain bore |
| Wheel hole (mm) | 50 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 4400 |
| Colour | Grey |
| Material | Avoantistatic Polyurethane |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 91 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | / |
| Ground clearance (mm) | / |
| Castor hole (mm) | / |
| Static load capacity (DaN) | / |
| Structure | / |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | / |