Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

**SERIE 18A** 

# 42BISB

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 100mm ean 28328

**Material:** Avolan Polyurethane

Core: Aluminum Application field:

Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

**EAN13**:8018793283281 **EAN5**:28328

5:28328 **Article code:**21042BF100ACU



## Flooring

- Asphalt
  - Concrete
  - Grid
  - Stoneware

#### **Features**

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 200 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

#### Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	200
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

### Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	150
Castor hole (mm)	I
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted