Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 14

# 30YDIR

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 125mm

Material:AvolanCore:CastApplication field:PolyurethaneIronIndustry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

#### **Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and a 4 position directional blocking device. Black epoxy paint.

Product line: Polyurethane

EAN13:/ EAN5:/ Article code:210304F125ZCU



### **Features**

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 500 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 91

## **Flooring**

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	125
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

### Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	106X076
Plate hole size (mm)	15
Offset (mm)	60
Ground clearance (mm)	185
Castor hole (mm)	1
Static load capacity (DaN)	630
Structure	Swivel
Version	Plate
Brake	Directional lock
Plain axle	1
Stem type	1
Finishing	Black painted