

SERIE 18A

37

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 150mm ean 29299

**Material:** Avolan  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Polyurethane

**EAN13:**8018793292993 **EAN5:**29299 **Article code:**RS03700150ACU



## Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 200 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	200
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

## Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	45
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized