Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 14

30YDIRBIS

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 250mm ean 19596

Material:AvolanCore:CastApplication field:PolyurethaneIronIndustry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and a 4 position directional blocking device. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793195966 **EAN5**:19596 **Article code**:210300F25DLCU



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 1400 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 91 • Sto

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1400
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	15
Offset (mm)	80
Ground clearance (mm)	305
Castor hole (mm)	1
Static load capacity (DaN)	1750
Structure	Swivel
Version	Plate with brake
Brake	Directional lock
Plain axle	1
Stem type	1
Finishing	Black painted