

SERIE 14

## 30YDIRBIS

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 250mm ean 19596

**Material:** Avolan  
Polyurethane

**Core:** Cast  
Iron

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and a 4 position directional blocking device. Black epoxy paint.

**Product line:** Polyurethane

**EAN13:**8018793195966

**EAN5:**19596

**Article code:**210300F25DLCU



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 1400 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 250                 |
| Band width (mm)             | 60                  |
| Hub width (mm)              | 60                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 25                  |
| Bearing seat (mm)           | 52X15               |
| Dynamic load capacity (DaN) | 1400                |
| Colour                      | Yellow              |
| Material                    | Avolan Polyurethane |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 91                  |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 135X110          |
| Plate hole spacing (mm)    | 105X080          |
| Plate hole size (mm)       | 15               |
| Offset (mm)                | 80               |
| Ground clearance (mm)      | 305              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 1750             |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Directional lock |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Black painted    |