

SERIE 14

30YDIR

AVO - Wheel with avolan polyurethane and steel castor for industry,
diameter 300mm ean 22054

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and a 4 position directional blocking device. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793220545

EAN5:22054

Article code:21N304F300LCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 1800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	1800
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	83
Ground clearance (mm)	370
Castor hole (mm)	/
Static load capacity (DaN)	2250
Structure	Swivel
Version	Plate
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted