

SERIE 18N-BN

## 37N-BN

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 80mm ean 28866

**Material:** Avolan  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel coated with cast black rounded polyurethane tread AVOLAN 91 Shore A and black matte aluminium centre. Quiet, robust and discreet, ideal for stage and theatre equipment. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, black painted, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Polyurethane

**EAN13:**8018793288668 **EAN5:**28866 **Article code:**0937N00080ACU



## Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 120 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 91

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 80                  |
| Band width (mm)             | 25                  |
| Hub width (mm)              | 30                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 12                  |
| Bearing seat (mm)           | 32X10               |
| Dynamic load capacity (DaN) | 120                 |
| Colour                      | Black               |
| Material                    | Avolan Polyurethane |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 91                  |

## Support data

|                            |               |
|----------------------------|---------------|
| Plate size (mm)            | 100X085       |
| Plate hole spacing (mm)    | 080X060       |
| Plate hole size (mm)       | 8,5X12        |
| Offset (mm)                | 37            |
| Ground clearance (mm)      | 108           |
| Castor hole (mm)           | /             |
| Static load capacity (DaN) | 150           |
| Structure                  | Swivel        |
| Version                    | Plate         |
| Brake                      | /             |
| Plain axle                 | /             |
| Stem type                  | /             |
| Finishing                  | Black painted |