

SERIE 18N-BN

18N-BN

AVO - Wheel with avolan polyurethane for industry, diameter 100mm ean 22235

Material: Avolan
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast black rounded polyurethane tread AVOLAN 91 Shore A and black matte aluminium centre. Quiet, robust and discreet, ideal for stage and theatre equipment. Hub on shielded ball bearings assembled with central spacer.

Product line: Polyurethane

EAN13:8018793222358 **EAN5:**22235 **Article code:**09018NB100LCN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 250 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	250
Colour	Black
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/