

SERIE 14-MG

## 14-MG

AVO - Wheel with avolan polyurethane for industry, diameter 260mm ean 29035

**Material:** Avolan Polyurethane    **Core:** Steel    **Application field:** Industry

**Description:**

Drive wheel with high-performance AVOLAN 91 Shore A polyurethane tread and steel core, ensuring high load capacity, excellent abrasion resistance and low rolling resistance. Particularly suitable for pallet trucks and material handling systems requiring reliability and long service life.

**Product line:** Polyurethane

**EAN13:**8018793290357    **EAN5:**29035    **Article code:**090143026095U



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 2000 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore A    **Hardness:** 92

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	260
Band width (mm)	95
Hub width (mm)	15
Hub version	Plain bore
Wheel hole (mm)	30
Bearing seat (mm)	/
Dynamic load capacity (DaN)	2000
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	92

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	2200
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/