

SERIE 14

14

AVO - Wheel with avolan polyurethane for industry, diameter 300mm ean 25436

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Polyurethane

EAN13:8018793254366

EAN5:25436

Article code:0901435300YCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 2200 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	80
Hub width (mm)	80
Hub version	Ball bearing
Wheel hole (mm)	35
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	2200
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/