Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 14

33YDIRTBIS

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 250mm ean 25617

Material: Avolan Polyurethane

Core: Cast Iron Application field:

Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of heavy-gauge pressed and welded steel, swivel-mounted on a thrust bearing and tapered roller bearings, with top plate and directional lock.Black epoxy coating.Equipped with ISO Twist Lock fitting and 4-position directional lock.

Product line: Polyurethane

EAN13:8018793256179

Features

EAN5:25617

Article code:21T33DF250GCU



Flooring

Minimum temperature: -20 Maximum temperature: 80 Dynamic Dynam

Hardness scale: Shore A

Dynamic load capacity: 2800 DaN

Hardness: 91

Asphalt

ConcreteGrid

• Stoneware

Wheel data

Rotation: Ball bearing

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	2800
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	1
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	230X230
Plate hole spacing (mm)	190X190
Plate hole size (mm)	19
Offset (mm)	80
Ground clearance (mm)	364
Castor hole (mm)	1
Static load capacity (DaN)	3500
Structure	Swivel
Version	Plate with brake
Brake	Directional lock
Plain axle	1
Stem type	1
Finishing	Black painted