Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 14

# 33YDIRTBIS

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 300mm ean 23882

**Material:** Avolan Polyurethane

Core: Cast Iron Application field:

Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

#### Twin Wheel Extra Heavy-Duty Castors:

Made of heavy-gauge pressed and welded steel, swivel-mounted on a thrust bearing and tapered roller bearings, with top plate and directional lock.Black epoxy coating.Equipped with ISO Twist Lock fitting and 4-position directional lock.

Product line: Polyurethane

EAN13:8018793238823

EAN5:23882

Article code:21T33DF300GCU



### **Features**

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 4000 DaN

Rotation: Ball bearing H

Hardness scale: Shore A

Hardness: 91

## **Flooring**

- Asphalt
- Concrete
- Grid Stoneware

### Wheel data

| Diameter (mm)               | 300                 |
|-----------------------------|---------------------|
| Band width (mm)             | 70                  |
| Hub width (mm)              | 70                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 30                  |
| Bearing seat (mm)           | 62X16               |
| Dynamic load capacity (DaN) | 4000                |
| Colour                      | Yellow              |
| Material                    | Avolan Polyurethane |
| Box pieces                  | 1                   |
| Hardness scale              | Shore A             |
| Hardness                    | 91                  |

### Support data

| Plate size (mm)            | 230X230          |
|----------------------------|------------------|
| Plate hole spacing (mm)    | 190X190          |
| Plate hole size (mm)       | 19               |
| Offset (mm)                | 83               |
| Ground clearance (mm)      | 419              |
| Castor hole (mm)           | 1                |
| Static load capacity (DaN) | 5000             |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Directional lock |
| Plain axle                 | 1                |
| Stem type                  | 1                |
| Finishing                  | Black painted    |