

SERIE 14

33YDIR

AVO - Wheel with avolan polyurethane and steel castor for industry, diameter 500mm ean 24872

Material: Avolan
Polyurethane

Core: Cast
Iron

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOLAN 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and directional lock. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793248723

EAN5:24872

Article code:21033DI501GCU



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 7500 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	500
Band width (mm)	100
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	40
Bearing seat (mm)	80X18
Dynamic load capacity (DaN)	7500
Colour	Yellow
Material	Avolan Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	315X315
Plate hole spacing (mm)	250X250
Plate hole size (mm)	21
Offset (mm)	100
Ground clearance (mm)	550
Castor hole (mm)	/
Static load capacity (DaN)	9000
Structure	Swivel
Version	Plate with brake
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted