

SERIE 19

88A

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 125mm ean 28381

Material: Avoplus
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793283816 **EAN5:**28381 **Article code:**21088A0125ACB



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 225 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X10
Dynamic load capacity (DaN)	225
Colour	Blue
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	/
Ground clearance (mm)	175
Castor hole (mm)	/
Static load capacity (DaN)	290
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized