

SERIE 19

88

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 150mm ean 28391

Material: Avoplus
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793283915

EAN5:28391

Article code:2108800150ACB



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	50
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted