

SERIE 19

89

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 160mm ean 28403

Material: Avoplus Polyurethane **Core:** Aluminum **Scope:** Industry

Description:

Wheel coated with cast Soft Polyurethane tread AVOPLUS 78 Shore A with high smoothness and high thickness. Aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793284035 **EAN5:**28403 **Article code:**2108900160ACB



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 1000 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	1000
Colour	Blue
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	72
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	1250
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted