

SERIE 19V-B30

88BV-B30

AVO - Wheel with avoplus polyurethane and steel castor for industry, diameter 200mm ean 28288

Material: Avoplus
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel with soft AVOPLUS polyurethane 78 Shore A, round tread R30 and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793282888

EAN5:28288

Article code:09088B020BACV



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 700 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 78

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	700
Colour	Green
Material	Avoplus Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	78

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	260
Castor hole (mm)	/
Static load capacity (DaN)	880
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted