

SERIE 18M-B

77BISB-B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 200mm ean 28362

Material: Avoprene
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A, rounded tread and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793283625

EAN5:28362

Article code:21077BF200ABM



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 800 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	800
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	260
Castor hole (mm)	/
Static load capacity (DaN)	1000
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Black painted