

SERIE 18M-B

## 77BIS-B

**AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 250mm ean 28358**

**Material:** Avoprene  
Polyurethane

**Core:**  
Aluminum

**Application field:**  
Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A, rounded tread and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

**Product line:** Polyurethane

**EAN13:**8018793283588

**EAN5:**28358

**Article code:**21077F0250ABM



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 800 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |                       |
|-----------------------------|-----------------------|
| Diameter (mm)               | 250                   |
| Band width (mm)             | 50                    |
| Hub width (mm)              | 60                    |
| Hub version                 | Ball bearing          |
| Wheel hole (mm)             | 20                    |
| Bearing seat (mm)           | 47X14                 |
| Dynamic load capacity (DaN) | 800                   |
| Colour                      | Brown                 |
| Material                    | Avoprene Polyurethane |
| Box pieces                  | /                     |
| Hardness scale              | Shore A               |
| Hardness                    | 91                    |

### Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 175X140          |
| Plate hole spacing (mm)    | 140X105          |
| Plate hole size (mm)       | 15               |
| Offset (mm)                | 80               |
| Ground clearance (mm)      | 305              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 1000             |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Rear             |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Black painted    |