

SERIE 18M-B

78-B

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 250mm ean 28366

Material: Avoprene
Polyurethane

Core:
Aluminum

Application field:
Industry

Description:

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A, rounded tread and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: Polyurethane

EAN13:8018793283663

EAN5:28366

Article code:2107800250ABM



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 2000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 91

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	2000
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

Support data

Plate size (mm)	230X230
Plate hole spacing (mm)	190X190
Plate hole size (mm)	19
Offset (mm)	80
Ground clearance (mm)	320
Castor hole (mm)	/
Static load capacity (DaN)	2500
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted