

SERIE 15

## 33DIRBIS

AVO - Wheel with avoprene polyurethane and steel castor for industry, diameter 300mm ean 28136

**Material:** Avoprene Polyurethane    **Core:** Cast Iron    **Scope:** Industry

**Description:**

Wheel coated with cast Polyurethane tread AVOPRENE 91 Shore A and mechanical black painted cast iron centre. Hub on shielded ball bearings assembled with central spacer.

**Twin Wheel Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and directional lock. Black epoxy paint.

**Product line:** Polyurethane

**EAN13:**8018793281362    **EAN5:**28136    **Article code:**13F33DI300GCA



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 4000 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 91

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	300
Band width (mm)	70
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	30
Bearing seat (mm)	62X16
Dynamic load capacity (DaN)	4000
Colour	Brown
Material	Avoprene Polyurethane
Box pieces	/
Hardness scale	Shore A
Hardness	91

### Support data

Plate size (mm)	230X230
Plate hole spacing (mm)	190X190
Plate hole size (mm)	19
Offset (mm)	83
Ground clearance (mm)	375
Castor hole (mm)	/
Static load capacity (DaN)	5000
Structure	Swivel
Version	Plate with brake
Brake	Directional lock
Plain axle	/
Stem type	/
Finishing	Black painted