

SERIE 139CD-S

# 140A-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 100mm ean 29106

**Material:** Conductive Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:**8018793291064 **EAN5:**29106 **Article code:**C6140A01000FG



## Features

**Minimum temperature:** -20 **Maximum temperature:** 60 **Dynamic load capacity:** 100 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

## Flooring

### Wheel data

Diameter (mm)	100
Band width (mm)	29
Hub width (mm)	39
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

### Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	120
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized