

SERIE 139CD-S

140B-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 100mm ean 29109

Material: Conductive
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13: 8018793291095

EAN5: 29109

Article code: C6140B01000FG



Features

Minimum temperature: -20	Maximum temperature: 60	Dynamic load capacity: 100 DaN
Rotation: Plain bore	Hardness scale: Shore A	Hardness: 85

Flooring

Wheel data

Diameter (mm)	100
Band width (mm)	29
Hub width (mm)	39
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	120
Structure	Swivel
Version	Axle
Brake	/
Plain axle	20X50
Stem type	Plain axle
Finishing	Galvanized