

SERIE 139CD-S

140ANTF-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 100mm ean 29118

Material: Conductive Rubber tyre

Core: Polypropylene

Application field: Industry

Description:

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Antistatic/Conductive

EAN13:8018793291187 **EAN5:**29118 **Article code:**C6140FA1000FG



Features

Minimum temperature: -20 **Maximum temperature:** 60 **Dynamic load capacity:** 100 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 85

Flooring

Wheel data

Diameter (mm)	100
Band width (mm)	29
Hub width (mm)	39
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	12
Static load capacity (DaN)	120
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized