

SERIE 139CD-S

## 140ANT-CD

**AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 125mm ean 29101**

**Material:** Conductive Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:**8018793291019

**EAN5:**29101

**Article code:**C61400A1250FG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 60

**Dynamic load capacity:** 110 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 85

## Flooring

## Wheel data

|                             |                        |
|-----------------------------|------------------------|
| Diameter (mm)               | 125                    |
| Band width (mm)             | 35                     |
| Hub width (mm)              | 50                     |
| Hub version                 | Plain bore             |
| Wheel hole (mm)             | 12                     |
| Bearing seat (mm)           | /                      |
| Dynamic load capacity (DaN) | 110                    |
| Colour                      | Grey                   |
| Material                    | Conductive Rubber tyre |
| Box pieces                  | /                      |
| Hardness scale              | Shore A                |
| Hardness                    | 85                     |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 100X085          |
| Plate hole spacing (mm)    | 080X060          |
| Plate hole size (mm)       | 8,5X12           |
| Offset (mm)                | 37               |
| Ground clearance (mm)      | 154              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 130              |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Front            |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |