

SERIE 139CD-S

# 140F-CD

**AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 125mm ean 29116**

**Material:** Conductive  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

**Product line:** Antistatic/Conductive

**EAN13:** 8018793291163

**EAN5:** 29116

**Article code:** C6140F01250FG



## Features

|                                 |                                |                                       |
|---------------------------------|--------------------------------|---------------------------------------|
| <b>Minimum temperature:</b> -20 | <b>Maximum temperature:</b> 60 | <b>Dynamic load capacity:</b> 110 DaN |
| <b>Rotation:</b> Plain bore     | <b>Hardness scale:</b> Shore A | <b>Hardness:</b> 85                   |

## Flooring

## Wheel data

|                                    |                        |
|------------------------------------|------------------------|
| <b>Diameter (mm)</b>               | 125                    |
| <b>Band width (mm)</b>             | 35                     |
| <b>Hub width (mm)</b>              | 50                     |
| <b>Hub version</b>                 | Plain bore             |
| <b>Wheel hole (mm)</b>             | 12                     |
| <b>Bearing seat (mm)</b>           | /                      |
| <b>Dynamic load capacity (DaN)</b> | 110                    |
| <b>Colour</b>                      | Grey                   |
| <b>Material</b>                    | Conductive Rubber tyre |
| <b>Box pieces</b>                  | /                      |
| <b>Hardness scale</b>              | Shore A                |
| <b>Hardness</b>                    | 85                     |

## Support data

|                                   |            |
|-----------------------------------|------------|
| <b>Plate size (mm)</b>            | /          |
| <b>Plate hole spacing (mm)</b>    | /          |
| <b>Plate hole size (mm)</b>       | /          |
| <b>Offset (mm)</b>                | 37         |
| <b>Ground clearance (mm)</b>      | 152        |
| <b>Castor hole (mm)</b>           | 12         |
| <b>Static load capacity (DaN)</b> | 130        |
| <b>Structure</b>                  | Swivel     |
| <b>Version</b>                    | Bolt hole  |
| <b>Brake</b>                      | /          |
| <b>Plain axle</b>                 | /          |
| <b>Stem type</b>                  | /          |
| <b>Finishing</b>                  | Galvanized |