

SERIE 139CD-S

140-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 80mm ean 29102

Material: Conductive
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Antistatic/Conductive

EAN13: 8018793291026 **EAN5:** 29102 **Article code:** C6140000800FG



Features

Minimum temperature: -20 **Maximum temperature:** 60 **Dynamic load capacity:** 80 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 85

Flooring

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	39
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	80
Colour	Grey
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	108
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized