

SERIE 139CD-S

# 140ANTB-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 80mm ean 29111

**Material:** Conductive Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

**Product line:** Antistatic/Conductive

**EAN13:**8018793291118 **EAN5:**29111 **Article code:**C6140BA0800FG



## Features

**Minimum temperature:** -20 **Maximum temperature:** 60 **Dynamic load capacity:** 80 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

## Flooring

## Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	39
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	80
Colour	Grey
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle
Finishing	Galvanized