

SERIE 139CD-S

# 139CD-S

AVO - Wheel with conductive rubber tyre for industry, diameter 80mm ean 28529

**Material:** Conductive Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with conductive non-marking grey rubber tyre 85 Shore A and thermoplastic centre. Hub on plain bore.

**Product line:** Antistatic/Conductive

**EAN13:**8018793285292    **EAN5:**28529    **Article code:**GC1390008030F



## Features

**Minimum temperature:** -20    **Maximum temperature:** 60    **Dynamic load capacity:** 90 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore A    **Hardness:** 85

## Flooring

## Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	39
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	90
Colour	Grey
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/