

SERIE 18

136A

AVO - Wheel with cushion rubber tyre and steel castor for industry,
diameter 250mm ean 28425

Material: Cushion Rubber
tyre

Core: Cast
Iron

Application field:
Industry

Description:

CUSHION rubber wheel tyre 69 Shore A and mechanical cast iron centre. Hub on shielded ball bearings assembled with central space.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793284257

EAN5:28425

Article code:13134A0250CC



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 3000 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 69

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	80
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	3000
Colour	Black
Material	Cushion Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	69

Support data

Plate size (mm)	230X230
Plate hole spacing (mm)	190X190
Plate hole size (mm)	19
Offset (mm)	/
Ground clearance (mm)	320
Castor hole (mm)	/
Static load capacity (DaN)	3750
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted