

SERIE 16NX

67X

AVO - Wheel with cut-resistant rubber tyre and aisi 304 stainless steel castor for industry, diameter 150mm ean 28831

Material: Cut-resistant
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:


Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre.
Hub on stainless steel roller bearings.

Heavy-Duty Castors:

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 304, with plate. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793288316 **EAN5:**28831 **Article code:**00X6700150NRB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 450 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	50
Hub version	Stainless steel roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	450
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	201
Castor hole (mm)	/
Static load capacity (DaN)	560
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel