

SERIE 16N

66ANTF

AVO - Wheel with cut-resistant rubber tyre and steel castor for industry, diameter 150mm ean 28556

Material: Cut-resistant Rubber tyre

Core: Polyamide 6

Application field: Industry

Description:

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793285568

EAN5:28556

Article code:00066FA150NRG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	182
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole with brake
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized