

SERIE 16N

66

AVO - Wheel with cut-resistant rubber tyre and steel castor for industry, diameter 160mm ean 28145

Material: Cut-resistant Rubber tyre **Core:** Polyamide 6 **Scope:** Industry

Description:

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793281454 **EAN5:**28145 **Article code:**0006600151NCB



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 300 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	185
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized