

SERIE 16

45BISB

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 150mm ean 28434

Material: Elastic Rubber tyre **Core:** Cast Iron **Scope:** Industry

Description:

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre. Hub on shielded ball bearings assembled with central space.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with stem and rear brake. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793284349 **EAN5:**28434 **Article code:**14045BF150ECG



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	45
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	205
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Black painted